MATERIAL SAFETY DATA SHEET

(This MSDS complies with 29 CFR 1910.1200)

Product Name:	BC8400 Urethane Casting, Part B	BCC PRODUCTS, INC.	HMIS
Product Class:	Polyol Mixture	2140 Earlywood Drive	H - 1
Issue Date:	05/31/08	P.O. Box 327	F - 2
Approved By:	Robert R. Holmes	Franklin, IN 46131	R - 0
•		317-736-4090	P - H

24 HOUR EMERGENCY NO. 1-800-424-9300 CHEMTREC

SECTION 1 - HAZARDOUS INGREDIENTS

Chemical Name	Wt. % (optional)	OSHA (PEL)	ACGIH (TLV)	CAS NO.
Polyether Polyol		N.E	N.E.	9051-49-4
Diisodecyl Phthalalte		N.E.	N.E.	026761-40-0
Triethylenediamine		N.E	N.E.	280-57-9

SECTION 2 - PHYSICAL DATA

Boiling Point:	> 300 ° F	Specific Gravity (H20=1):	1.10
Vapor Pressure (mm Hg):	N.E.	Vapor Density (Air = 1):	N.E.
Solubility in Water:	Slight	Reactivity in Water:	None

Appearance and odor: Opaque liquid, slight odor.

SECTION 3 - FIRE AND EXPLOSION HAZARD

Flash Point:	>200 ° F	Flammable Limit:	LEL:	N.A.
Method Used:	T.O.C.	(In Air % by volume)	UEL:	N.A.

Auto Ignition Temperature: *N.A.*

Extinguishing Media: Carbon Dioxide, dry chemical, chemical foam, water spray.

Fire & Explosion Hazards: None Known.

Fire Fighting Procedures: Fire fighters must wear self-contained breathing apparatus to protect

against toxic and irritating vapors. Full protective clothing should also

be worn.

SECTION 4 - REACTIVITY DATA

Stability: Stable.

Conditions to Avoid: Temperatures above 120 ° F or below 32 ° F.

Incompatibility (Materials to avoid): Moisture and isocyanates.

Hazardous Decomposition Products: Carbon dioxide and carbon monoxide.

Hazardous Polymerization: Will not occur.

BC8400 URETHANE CASTING, Part B - Page 2

SECTION 5 - ENVIRONMENTAL AND DISPOSAL INFORMATION

Spill: Remove spillage by absorbing in sand, vermiculite, sawdust, or absorbent sweeping

compound. For small spills, rubbing alcohol may be used. Dike to prevent entry into

water system.

Disposal: Use approved incineration in accordance with federal, state and local environmental

regulations. Material must be disposed of in approved landfill.

SECTION 6 - HEALTH AND FIRST AID INFORMATION

Routes of Entry FIRST AID

Inhalation: Remove victim to uncontaminated area, administer oxygen if necessary. Seek medical

attention.

Eyes: Flush with water for 15 minutes. Seek medical attention.

Skin: Remove contaminated clothes and wash affected areas with soap and water. Seek

medical attention.

Ingestion: Dilute with water. INDUCE vomiting. Never give fluids or induce vomiting if victim is

unconscious or having convulsions. Seek medical attention.

EFFECTS OF OVER EXPOSURE

Acute: Eye contact may result in irritation. Inhalation of vapors may result in respiratory

irritation. Ingestion of the liquid may result in gastric disturbances.

Chronic: There are no known chronic effects associated with this material.

Existing Health

Conditions: N.D.A.

Carcinogen: NTP (National Toxicology Program): No IARC (Monographs): No OSHA: No

SECTION 7 - SPECIAL HANDLING & STORAGE PRECAUTIONS

Should be stored in a ventilated storage area between 65-85 ° F. Avoid excessive temperatures. Storage must be in tightly sealed containers to protect from moisture.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: If the PEL is exceeded, wear a NIOSH approved organic mist respirator.

Ventilation: Use local exhaust to maintain concentration below the PEL. Eye Protection: Fitted chemical goggles, face shield or safety glasses.

Personal Protection: Rubber gloves, boots and rubber apron to avoid skin contact. Contaminated

clothing or equipment should be cleaned or disposed of, after use.

Hygienic Practices: Educate and train employees on safe use of product. Shower and eye wash

station should be available.